



# PRODUCT SPECIFICATION LPT-M-HCN Transmitter

## Digital (Modbus®) Transmitter with Electrochemical Hydrogen Cyanide (HCN) Sensor

<b>Dimensions: Size</b>	5.0" X 5.0" X 2.8" (127 mm x 127 mm x 71 mm) (dimensions without optional splash guard)
<b>Weight</b>	5.0" X 5.0" X 3.3" (127 mm x 127 mm x 84 mm) (dimensions with optional splash guard) 14 ounces (400 g)
<b>Construction</b>	ABS / Polycarbonate blend, water/dust tight, corrosion resistant (meets IP54 standard with optional splash guard installed)
<b>Sensor: Type</b>	Electrochemical
<b>Life Span</b>	Approximately 18-24 months (application dependent)
<b>Gases Detected</b>	Hydrogen Cyanide (HCN)
<b>Sensor Range</b>	0 - 30 ppm standard
<b>System Power</b>	3-wire: VDC: 12-30 VDC, 3-Watts 4-wire: VAC: 12-27VAC, 3-VA
<b>Temperature</b>	-20°C to +40°C (-4°F to 104°F), -40°C (-40°F) with LCD heater option
<b>Humidity</b>	15 to 90% non-condensing
<b>Indicators</b>	LCD digital display, back lit, 128 X 64 pixel graphic (optional heater - applications to -40C)
<b>Signal</b>	Modbus® RS-485 RTU
<b>Relay</b>	One dry contact relay rated 2-amps @ 30v S.P.D.T.
<b>Audible</b>	Internal audible alarm (user controlled)
<b>Minimum Detection</b>	0.2ppm (with regular calibration maintenance of sensor)
<b>Accuracy</b>	+/- 0.25 ppm @ STP, across measurement range at time of calibration and at calibration concentration + calibration gas concentration error
<b>Repeatability</b>	No data available
<b>Sensitivity Drift</b>	<5% per month
<b>Response Time</b>	<30 seconds T <sub>90</sub> (calculated from 2-minute exposure time)
<b>Resolution</b>	Display resolution 0.2 ppm, sensor resolution: 0.15 ppm
<b>Warm Up Time</b>	5- minutes after power up (to full operation)
<b>Cross Sensitivity</b>	Arsine 0.2 = 1-ppm, Diborane 0.25 = 0.4 ppm, NO <sub>2</sub> 10 ppm = -19 ppm
<b>Safety</b>	Automatic resetting thermal overload fuse (reset capabilities to 500 times)
<b>Wiring</b>	4-wire VAC/VDC, 16 awg, 4-conductor shielded network wiring (daisy chain)
<b>Sensor Mounting</b>	Heavier than air (6' from floor, application dependent)
<b>Monitoring Area</b>	3000 - 5000 sq. ft. (application dependent)
<b>Certifications</b>	CSA: C22.2 NO.205-12 UL: UL508 (Edition 17): 2007 CE: EMC Directive 2004/108/EC, EN50270:2006, Type-1 & EN61010 FCC
<b>Note</b>	HCN is a colourless, extremely poisonous & flammable dangerous gas that boils at slightly above room temperature

Rev. 1803-1