

FEATURES

- Measuring Range 600A.
- With 0.01A High Resolution.
- 1ms Peak Hold Function.
- Data Hold Function.
- Auto Power Off.
- Autoranging.
- Back Light Function.
- Capacitor Function.
- TEMP Function.
- DC μ A Function

GENERAL SPECIFICATIONS

- **Numerical Display:**
4 digital liquid crystal(LCD), Maximum reading 6000.
- **Low Battery Indication:** The is displayed.
- **Sampling Rate:** 3 Times/sec
- **Power Source:** 1.5V size AAA battery x 2
- **Auto Power Off:** 15 minute.
- **Operating Temperature and Humidity:**
0°C to 40°C(32°F to 104°F); < 80%RH
- **Storage Temperature and Humidity:**
-10°C to 60°C(14°F to 140°F); < 70%RH
- **Jaw Opening Diameter:** 23mm
- **Dimensions:** 209×74×36mm(8.2"×2.9"×1.4")
- **Weight:** Approx.255g
- **Accessories:**
Carrying case, Batteries, Test Lead , Thermo Probe & Instruction Manual.

ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACA	60A	0.01A	±1.9%rdg+5dgts
	600A	0.1A	
DC μA	600A	0.1 μ A	±1%rdg+5dgts
ACV	600V	0.1V	±1.2%rdg+5dgts
DCV	600V	0.1V	±1%rdg+2dgts
Ohms	600 Ω	0.1 Ω	±1.5%rdg+3dgts
	6K Ω	0.001K Ω	
	\rightarrow)	Active Sound Level: \leq 40 Ω	
Cap	600 μ F	0.1 μ F	±2.5%rdg+5dgts
	6000 μ F	1 μ F	
Temp	-50.0~600.0°C	0.1°C	±1%rdg+1.5°C
	-58.0~999.8°F	0.2°F	±1%rdg+2.8°F



* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER
CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com

Distributed by:



Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130
Thailand. TEL: 0-2995-4461-3, FAX: 0-2995-4464
www.apl-asia.com
EMAIL: sales@apl-asia.com
LINE@: @APL-ASIA