

CENTER 326 Sound Level Calibrator



FEATURE :

- **Conforms to IEC 60942 (2003) class 2, ANSI S1.40-1984**
- **94dB and 114dB sound calibrator at 1kHz**
- **Accurate and simple to use**
- **Fits 1 inch and 1/2 inch microphones**



SPECIFICATION:

Output sound pressure levels	114dB and 94dB re 20uPa under reference conditions
Output frequency	1000Hz+/-2%
Total harmonic distortion	<3%
Reference conditions	Temperature 23 (73) Static pressure 101.325kpa Relative humidity 50%
Accuracy of sound pressure level	Understated reference environment conditions +/- 0.5dB
Battery type	One 9V battery 006P
Battery test	Operate: Green LED indicator Low battery: Red LED indicator
Battery life	Approx. 40hours
Dimensions	113mm(L) X 63mm(W) X 44mm(H)
Weight	Approx. 170g
Operating temperature	0 to 40
Storage temperature	-10 to 60
Accessories	9V battery, carrying case, instruction manual, 1/2inch microphone adapter.

CENTER
CENTER TECHNOLOGY CORP.

4/F., No.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail:center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com



Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand.
TEL. 0-2995-4461-3, FAX. 0-2995-4464
www.apl-asia.com
EMAIL : sales@apl-asia.com
LINE@ : @APL-ASIA