


CENTER 325 SOUND LEVEL METER



FEATURE

- **Mini Size**
- **Newly Design Shape**
- **Low Cost High Performance**
- **MAX/MIN Function**
- **Level Range Display**
- **AC Signal Output**
- **Resolution 0.1dB**
- **IEC 651 TYPE II**

Real Time Display With MAX MIN Recording



Level Range Display

SPECIFICATIONS

Level Range: Lo= 30-80 dB

Med= 50-100 dB

Hi= 80-130 dB

Accuracy: ± 1.5 dB(ref 94dB @1KHz)

Frequency Weighting: A, C

Time Weighting: Fast, Slow

Dynamic Range: 50 dB

Frequency Range: 31.5Hz to 8KHz

Microphone: Electret condenser microphone

Auxiliary Outputs: AC Signal Output

Battery Type: 9V, NEDA 1604, IEC 6F22, JIS 006P

Battery Life: 60 hours (with alkaline battery)

Operating Condition: 0°C to 40°C (<80%RH)

Storage Condition: -10°C to 60°C(<70%RH)

Dimensions: 232×54×34mm (9.1"×2.1"×1.3")

Weight: Approx.200g

Accessories: Battery, Manual, Calibration Screwdriver
Windscreen.

* The specifications and other information in this catalogue are subject to change without prior

CENTER®

CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com



Authorized Distributor
APL ASIA CO., LTD.

11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand.
TEL. 0-2995-4461-3, FAX. 0-2995-4464

www.apl-asia.com
EMAIL : sales@apl-asia.com
LINE@ : @APL-ASIA