

CENTER 337 LIGHTMETER

● FEATURE

- 5 Digital Display
- Auto Ranging
- Automatic Power Off
- Fc / lx Function Selectable
- HOLD Function
- Range Display
- Automatic Zero When Power On



● SPECIFICATIONS

- Light Range: 0.000~4000 fc
0.00~40000 lx
- Sample Rate: 2 times/sec
- Auto Power Off: 30 minutes
- Low Battery Indication: The  is displayed.
- Battery Type: 9V, NEDA 1604, IEC 6F22, JIS 006P
- Battery Life: 150 hours approx.
- Operation Temperature: 0°C to 40 °C
- Storage Temperature: -10°C to 60 °C
- Dimensions: 196mm(L) x 54mm(W) x 34mm(H)
- Weight: approx. 180g

Use CENTER 337 Lightmeter to monitor the illumination of working environment. This will ensure the comfortable and healthy working condition.



* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®

CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com

Distributed by:



Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130
Thailand. TEL. 0-2995-4461-3, FAX. 0-2995-4464
www.apl-asia.com
EMAIL: sales@apl-asia.com
LINE@: @APL-ASIA