



FEATURES

- CO₂, humidity and temperature measurement
- Dual wavelength NDIR CO₂ sensor (Non-Dispersive Infrared) for superior stability.
- User operated CO₂ calibration
- Data Hold & Max/Min/STEL/TWA function
- Adjustable auto power off timer
- Internal CO₂ alarm buzzer
- Backlight display function
- Datalogging up to 32,000 sets
- USB interface ,PC software included

SPECIFICATIONS

| |
|--|
| Measurement Range: CO ₂ : 0 ~ 30000 ppm Temperature: 0 to 50°C (32 to 122°F) Humidity: 0 ~ 100%RH |
| Accuracy: CO ₂ : ± (75 ppm + 3% of reading) (0 ~ 5000 ppm) Temperature: ± 1.0°C Humidity: ± 4.5%RH |
| Resolution: 1 ppm, 0.1°C/0.1°F, 0.1%RH |
| Response Time: 20 seconds |
| Battery Type: 9V alkaline battery |
| Battery life: Approximately 10 hours normal use (alkaline battery) |
| Operating Condition: 0°C to 50°C(< 90%RH) |
| Storage Condition: -20°C to 60°C(< 75%RH) |
| Dimensions: 226.5 x 65 x 38.5 mm |
| Weight: 273 g |
| Accessories: 9V Battery · Instruction Manual · micro USB cable · Windows software · Carrying case. |

★ **NEW!**



LED Back Light



Certificate No. 49Q13377

CENTER[®]
CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
 New Taipei City 238, Taiwan
 TEL: 886-2-26763926 E-Mail : center@centertek.com
 FAX: 886-2-26763925 http : //www.centertek.com

* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by:



Authorized Distributor
 APL ASIA CO., LTD.
 11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand.
 TEL. 0-2995-4461-3, FAX. 0-2995-4464
 www.apl-asia.com
 EMAIL : sales@apl-asia.com
 LINE@ : @APL-ASIA