

# CENTER 317

# HUMIDITY TEMPERATURE METER

(DEW POINT & WET BULB)



CE

### **Feature:**

- Dew Point and Wet Bulb temperature Measurement.
- Fast response.
- Auto shut off for Battery Saving.
- MAX/MIN Function.
- Dual displays:  
Primary display for Humidity;  
Secondary displays for temperature.

**CENTER**®



# CENTER 317 HUMIDITY TEMPERATURE METER

## SPECIFICATIONS

### Measurement Range:

Temperature: -20°C~60°C ; -4°F~140°F

Humidity: 0%RH~100%RH

Resolution: 0.1°C/0.1°F/0.1%RH

### Accuracy:

Temperature:  $\pm 0.8^{\circ}\text{C}$ ,  $1.6^{\circ}\text{F}$

Humidity:  $\pm 2.5\%RH$

Sampling Rate: 2 times/sec

### Humidity Sensor:

Electronic capacitance polymer film sensor.

Battery Type: 1.5V AA size battery x 4

Operating Condition: 0°C to 40°C (<80%RH)

Dimensions: 210×65×43mm

Accessories: Batteries, Instruction Manual

## Dual Display



Primary display for Humidity;  
Secondary displays for temperature.



CE



LED Back Light

1:1 Size



33%RH / 75%RH Humidity Standard (OPTIONAL)

\* The specifications and other information in this catalogue are subject to change without prior notice.

**CENTER**<sup>®</sup>  
**CENTER TECHNOLOGY CORP.**

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan  
TEL: 886-2-26763926 E-Mail: center@centertek.com  
FAX: 886-2-26763925 http://www.centertek.com

### Distributed by:



Authorized Distributor  
APL ASIA CO., LTD.  
11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130  
Thailand. TEL. 0-2995-4461-3, FAX. 0-2995-4464  
www.apl-asia.com  
EMAIL: sales@apl-asia.com  
LINE@: @APL-ASIA