mini FLOWATCH® 1 EVO



Economical mini solenoid pump, with alarm, for the condensate removal of air conditioners up to 10kW / 36000BTU.

Ref: DE05LCD600















Hose diameter
Suction: 4/6 mm - supplied
Discharge: 6/9 mm - not supplied

Flowrate max	13.2 l/h
Suction head max	1.5 m
Discharge head	10 m
Electrical power	19W
Voltage	220-240V 50/60Hz
Alarm	NC
Noise level*	())))
Protection rating	IP24
Thermal protection	Yes
Operating cycle**	100%
Power / alarm cable	1.5 m
Dimensions	88 x 30 x 45 / 75 x 36 x 38 mm

SPECIFICATIONS

^{**} The pump is able to run 100% of the time if necessary.



BENEFITS



Quick connectors

Make installation and maintenance easier.



Clear reservoir

Facilitates maintenance thanks to a quick visualization of the reservoir state.



Removable integrated filter

The reservoir has a metal filter that can be easily removed for quick cleaning.



Alarm function

The NC alarm on the mini FLOWATCH® 1 EVO allows to cut off the air conditioner power supply in the event of condensate overflow.



IP24 protection

Protected against water splashes.



Accessories included

Necessary accessories are supplied in the box.



CONTENTS

Pump - Reservoir with air-vent tube - Double-side adhesive - Inlet tube - Suction tube 1.5m - 3 clamps



APL ASIA CO., LTD. 11/129-132 Moo.5 Lamlukka Rd.,T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand. TEL. 0-2995-4461-3, FAX. 0-2995-4464 www.apl-asia.com EMAIL : sales@apl-asia.com

LINE@:@APL-ASIA

Authorized Distributor

^{*} Notation from 1 wave (≤ 20 dBA) to 6 waves (> 45 dBA)