

MGS-460 Sensor Specifications

PART NUMBER	REPLACEMENT SENSOR	TARGET GAS	SENSOR TECHNOLOGY ¹	FULLSCALE RANGE	ALARM RANGE	LOW ALARM	HIGH ALARM	ACCURACY (% OF RANGE)	TEMPERATURE RANGE
6302-4003	6302-9003	O ₂	EC	30% Volume	4.5%-30% Vol	19.5% Vol	23% Vol	±5%	-20°C to 50°C
6302-4026	6302-9026	NH ₃	EC	100ppm	15-100ppm	50ppm	90ppm	±5%	-40°C to 40°C
6302-4028	6302-9028	NH ₃	EC	1,000ppm	150-1,000ppm	500ppm	900ppm	±5%	-40°C to 40°C
6302-4029	6302-9029	NH ₃	EC	300ppm	10-300ppm	25ppm	150ppm	±5%	-40°C to 40°C
6302-4037	6302-9037	NH ₃	EC	5,000ppm	750-5,000ppm	2,500ppm	4,500ppm	±5%	-20°C to 40°C
6302-4040	6302-9040	CO	EC	500ppm	20-500ppm	25ppm	100ppm	±5%	-40°C to 50°C
6302-4041	6302-9041	NO ₂	EC	20ppm (20,000 ppb)	3,000-20,000ppb	5,000ppb	10,000ppb	±5%	-20°C to 40°C
6302-4052	6302-9052	R-600	IR	100% LEL (1.4% Vol)	15-100% LEL	50% LEL	90% LEL	±5%	-40°C to 50°C
6302-4053	6302-9053	R-50	IR	100% LEL (4.4% Vol)	15-100% LEL	50% LEL	90% LEL	±5%	-40°C to 50°C
6302-4054	6302-9054	R-290	IR	100% LEL (1.7% Vol)	15-100% LEL	50% LEL	90% LEL	±5%	-40°C to 50°C
6302-4069	6302-9069	NH ₃	CT	0-3% Volume	1 - 3.0% Vol	1% Vol	2% Vol	±5%	-40°C to 50°C
6302-4070	6302-9070	NH ₃	CT	0-100% LEL (15% Vol)	15 - 100% LEL	25% LEL	50% LEL	±5%	-40°C to 50°C
6302-4090	6302-9090	CO ₂	IR	5,000ppm	750-5,000ppm	2,500ppm	4,500ppm	±5%	-40°C to 50°C
6302-4091	6302-9091	CO ₂	IR	10,000ppm	1,500-10,000ppm	5,000ppm	9,000ppm	±5%	-40°C to 50°C
6302-4092	6302-9092	CO ₂	IR	20,000ppm	3,000-20,000ppm	10,000ppm	18,000ppm	±5%	-40°C to 50°C
6302-4093	6302-9093	CO ₂	IR	30,000ppm	4,500-30,000ppm	15,000ppm	27,000ppm	±5%	-40°C to 50°C
6302-4094	6302-9094	CO ₂	IR	40,000ppm	6,000-40,000ppm	20,000ppm	36,000ppm	±5%	-40°C to 50°C
6302-4095	6302-9095	CO ₂	IR	50,000ppm	7,500-50,000ppm	25,000ppm	45,000ppm	±5%	-40°C to 50°C
6302-4101	6302-9101	R-134a	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4103	6302-9103	R-404A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4105	6302-9105	R-407A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4107	6302-9107	R-410A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4109	6302-9109	R-22	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4111	6302-9111	R-507A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C

¹ EC = Electrochemical Cell, IR = Infrared, CT = Catalytic Bead, SC = Metal-Oxide Semiconductor



PART NUMBER	REPLACEMENT SENSOR	TARGET GAS	SENSOR TECHNOLOGY ¹	FULLSCALE RANGE	ALARM RANGE	LOW ALARM	HIGH ALARM	ACCURACY (% OF RANGE)	TEMPERATURE RANGE
6302-4123	6302-9123	R-407C	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4126	6302-9126	R-407F	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4152	6302-9152	HFO1234ze	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4155	6302-9155	R-32	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4156	6302-9156	R-448A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4157	6302-9157	R-452A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4158	6302-9158	R-513A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4159	6302-9159	R-434A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4160	6302-9160	R-450A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4161	6302-9161	HFO1234yf	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4163	6302-9163	R-452B	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4164	6302-9164	R-454A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4165	6302-9165	R-422A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4166	6302-9166	R-422D	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4167	6302-9167	R-427A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4169	6302-9169	R-449A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4170	6302-9170	R-454C	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4171	6302-9171	R-454B	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4172	6302-9172	R-455A	SC	1,000ppm	150-1,000ppm	500ppm	900ppm	-10%/+15%	-40°C to 50°C
6302-4301	6302-9301	R-290	SC	5,000ppm	750-5,000ppm	800ppm	2,500ppm	-10%/+15%	-40°C to 50°C
6302-4310	6302-9310	R-290	SC	2,500ppm	400-2,500ppm	1,000ppm	2,000ppm	-10%/+15%	-40°C to 50°C

¹ EC = Electrochemical Cell, IR = Infrared, CT = Catalytic Bead, SC = Metal-Oxide Semiconductor

