

# Controllers



VS



LCD display, push buttons, LEDs	Interface	Full colour LCD touch screen, LEDs
4	# of Channels	128
Three SPDT 5 amp @ 240 VAC	Relays	Four SPDT 5 amp @ 240 VAC
Standard or water tight	Internal Alarm	Standard or extra loud or water tight
LPT, LPT-A, LPT-M, LPT-P, ART, CXT, AST-IS	Remote Transmitters	LPT, LPT-A, LPT-M, LPT-P, ART, CXT, AST-IS
QCC-RDM Remote Display LNK-AO Analog Output LNK-XT Network Extender RLY-4 Remote Relays RPS24VDC Remote Power Supply	Peripheral Devices	FCS-RDM Remote Display LNK-AO Analog Output LNK-AI Analog Input LNK-XT Network Extender RLY-4 Remote Relays RLY-8 Remote Relays RPS-24VDC Remote Power Supply
Modbus®, four 4-20 mA	Input	Modbus®, four to eight 4-20 mA
Modbus®, BACnet®, 1 strobe/horn drive	Output	Modbus®, BACnet®, 2 strobe/horn drives
2 analog outputs with datalogging, internal heater, top mounted strobe, shutoff switch, water tight alarm	Options	4 to 8 analog outputs, 4 to 8 analog inputs, internal heater, top mounted strobe, water tight alarm