

INSTALLER SUPPLIED LOW VOLTAGE TERMINALS (24V NOMINAL)

SELECT LOW or LINE VOTAGE INCOMING POWER TO DCC, NOT BOTH

RELAY CONTROL WIRING TERMINALS. CONNECT TO COM & N/C. DO NOT USE SOLID CORE WIRE

INSTALLER SUPPLIED OPTIONAL LINE VOLTAGE (90-240 VAC, 50-60 HZ)

INTERNAL ELECTRO-CHEMICAL NO₂ SENSOR AND SPLASH GUARD




INTERNAL ELECTROCHEMICAL NO₂ SENSOR AND SPLASH GUARD



INSIDE DOOR LPT

LPT-END 3-WIRE ANALOG TRANSMITTER WIRED TO DCC DUAL CHANNEL CONTROLLER



THIS DCC-D-NO2B-RT-S / LPT-END-S COMBINATION MAKES A TWO CHANNEL GAS DETECTION SYSTEM FOR MONITORING NO₂ IN SPRAY DOWN APPLICATIONS.

CRITICAL ENVIRONMENT TECHNOLOGIES CANADA INC.
 www.critical-environment.com
 DCC-D-NO2B-RT-S C/W LPT-END-S 3-Wire WIRING CONNECTION PHOTO DRAWING
 REV-A June 9, 2016