

ABM-HOOD & ABM-HOOD-200
ABM EasyHood

The ABM EasyHood captures air speed values from air supply or return/exhaust grilles in residential or commercial buildings, and easily converts that into an airflow volume reading. To accomplish this, the ABM EasyHood is used with an ABM-200 Airflow & Environmental Meter (or ABM-100 Airflow Meter) and a smartphone having the latest, free, CPS Link™ app installed.

KEY FEATURES:

- Test and Balance reports - automatically generated
- Easy, accurate and affordable HVAC airflow measurement in a lightweight, compact housing
- Measures airflow in grilles up to 12" x 12" (.3m x .3m) or up to 24" x 24" (.6m x .6m) with the included Expansion Hood
- Use smartphone and free CPS Link™ app to display, store and send data
- Also measures temperature, wet bulb, dew point and relative humidity (ABM-200)
- Accuracy, calibration, certification - in accordance with ANSI / AMCA standards

ADDITIONAL FEATURES WHEN USED WITH FREE CPS LINK™ APP

- Client Lists- Enter and retain client information
- Job Tracker- Create and retain record of services performed
- Geolocation- Record where (global coordinates) and when (time stamp) tests performed



**Smartphone not included*



Up to 12" x 12"
 (.3 x .3 m) grilles



Up to 24" x 24"
 (.6 x .6 m) grilles

Easy, Convenient Display Screens (When Using ABM-200 or ABM-100 and CPS Link App)

Regular Airflow Test
 [35-1,200 CFM (59-2,039 M³/H)]

Airflow Volume (CFM, M³/H, MAX, AVG, MIN)

Low Volume Airflow Test
 [7-100 CFM (12-170 M³/H)]

Airflow Volume (CFM, M³/H, MAX, AVG, MIN)



CPS Link™
 US Patent No. 9,043,161



Version 4.3 or higher



Connect with us on social media



ABM EasyHood



ABM-HOOD & ABM-HOOD-200 include:



Airflow capture hood




Expansion hood accessory



Low airflow adapter



Color box



Padded carrying case



Owner's manual

SPECIFICATIONS

ABM-HOOD

Hood Opening	12" x 12" (.3 m x .3 m)
Expansion Hood Opening	24" x 24" (.6 m x .6 m)
Weight (with Expansion Hood)	4.75 lb. (2.15 kg)
Hood Size (with Expansion Hood)	17.75" H x 25" W x 25" D (.45 m x .63 m x .63 m)

ABM-HOOD-200 (When Used With ABM-200 Meter)

Wireless Connection Range	≤100 ft. (30.5 m)	
Airflow Volume Regular Test	Range: 35-1,200 CFM (59-2,039 M ³ /H)	
Airflow Low Volume Test	Range: 7-100 CFM (12-170 M ³ /H)	
RH Range	Range: 0-85%	Accuracy: ±4%
Operating Temperature	Range: 0 °F to 140 °F (-18 °C to 60 °C)	Accuracy: ±0.7 °F (0.4 °C)
Auto Power Off	No connection or 30 sec after closing app	
Battery Type (3.0 V)	Inside ABM-200 (CR2450 Coin Cell, Lithium)	
Battery Life	> 500 hrs.	

Calibration, Certification
Accuracy verified in accordance with ANSI AMCA 201-207 Airflow Rate Device Verification. Airflow calibration and certification tests performed at a 3rd party AMCA Certified Laboratory in accordance with ANSI/AMCA 210-ANSI/AMCA 51 test methods.

Warranty
1 Year (including ABM-HOOD)

PACKAGING

	ABM-HOOD & ABM-HOOD-200	ABM-HOOD	ABM-HOOD-200	ABM-HOOD or ABM-HOOD-200	ABM-HOOD	ABM-HOOD-200
	H x W x D, In (cm)	Weight, Lbs (kg)	Weight, Lbs (kg)	Product Qty Per	UPC	UPC
Color Box	14.12" x 16.62" x 16.75" (36 x 42 x 43 cm)	9.56 lbs (4.33 kg)	9.81 lbs (4.44 kg)	1	750377103094	750377103100
Corrugated Shipping Box	15.25" x 17" x 17.5" (39 x 43 x 45 cm)	11.5 lbs (5.21 kg)	11.75 lbs (5.32 kg)	1		

Included with ABM-HOOD-200



ABM-200 Airflow & Environmental Meter

Purchased Separately



ABM-100 Airflow Meter