

# CENTER 20 CLAMP METER

We optimized the cost to sell for less but never wanted to sacrifice any performance. The new CENTER 20 is built on quality. It is robust and reliable. The basic clamp meter functions with AC current measurement are more than proficient for most of general electricians or equipment installers in the field. Also, it's rated 600V CAT III, it's safe to use.



~Lower Price Tag comes  
with the Highest Value~

**CENTER**<sup>®</sup>  
**CENTER TECHNOLOGY CORP.**

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan  
TEL: 886-2-26763926 E-Mail: center@centertek.com  
FAX: 886-2-26763925 http: //www.centertek.com

## GENERAL SPECIFICATIONS

- **Numerical Display:**  
3 3/4 digital liquid crystal(LCD), Maximum reading 3999.
- **Low Battery Indication:** The is displayed.
- **Sampling Rate:** 2 Times/sec
- **Power Source:** 1.5V size AAA battery x 2
- **Auto Power Off:** 10 minute.
- **Operating Temperature and Humidity:**  
0°C to 40°C(32°F to 104°F); < 80%RH
- **Storage Temperature and Humidity:**  
-10°C to 60°C(14°F to 140°F); < 70%RH
- **Jaw Opening Diameter:** 25.4 mm
- **Dimensions:** 203(L)×75(W)×32(H)mm
- **Weight:** Approx.262g
- **Accessories:** Batteries, Test Lead, Instruction Manual.

## ELECTRICAL SPECIFICATIONS

### DCV (Aurorance)

Range	Resolution	Accuracy	Input Impedance	Overload Protection
400V	0.1V	1% + 3	1MΩ	660Vrms
600V	1V			

### ACV (Aurorance)

Range	Resolution	Accuracy	Input Impedance	Overload Protection
		50Hz~400Hz		
400V	0.1V	1.2% + 3	1MΩ	660Vrms
600V	1V			

### ACA (Aurorance)

Range	Resolution	Accuracy		Overload Protection
		50Hz~60Hz	60Hz~400Hz	
40A	0.01A	1.9% + 3	3.0% + 5	600Vrms
400A	0.1A			

### Ohm (Ω)

Range	Resolution	Accuracy	Input Impedance	Overload Protection
400Ω	1Ω	1% + 2	-1.5V DC	600Vrms

### Continuity ( )

Range	Active Region	Max Test Voltage	Overload Protection
	< 25 Ohm	-1.5V DC	600Vrms

\* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by: