

CENTER 24 Flexible AC Current Meter

FEATURES

★ **NEW!**



- Compact, Lightweight And Simple To Use.
- 3 Selectable Current Measurement Ranges: 4A/40A/400A AC.
- Resolution: 0.001A/ 0.01A / 0.1A.
- Direct Current Readings.
- True-Rms Measuring.
- 8" Flexible Sensor Fit Around Conductors Up To 2.8" In Diameter.
- 5.5mm Coil Diameter Allows Measurement In Tight Spaces. (Double Insulated)
- 1.5m (5 ft) Cable.
- EN 61010 CAT IV 600V, CAT III 1000V.



ELECTRICAL SPECIFICATIONS

Model	CENTER 24 True RMS
Measuring Ranges	4A / 40A / 400A
Resolution	0.001A / 0.01A / 0.1A
Accuracy	3% $\pm$ 5 digits
Power Supply	UM-4 or AAA 1.5V battery x2 (alkaline battery)

* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER[®]
CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
 New Taipei City 238, Taiwan
 TEL: 886-2-26763926 E-Mail : center@centertek.com
 FAX: 886-2-26763925 http : //www.centertek.com

Distributed by: