

CENTER 27/28 AC TRMS CLAMP METER

★ AC 1000A!

FEATURES

- Slim and Lightweight Size.
- True RMS Measuring.
- Measuring Current : AC 1000A
- Data Hold Function.
- MinMax Function.(CENTER27)
- 1ms Peak Hold Function.(CENTER28)
- Capacitor Function.(CENTER28)
- Measuring Frequency From Current Clamp & Test Terminal. (CENTER28)
- Auto Power Off.
- Autoranging.

GENERAL SPECIFICATIONS

- **Numerical Display:**
4 digital liquid crystal(LCD), Maximum reading 6000.
- **Low Battery Indication:** The  is displayed.
- **Sampling Rate:** 2 Times/sec
- **Power Source:** CR2032(3VDC) battery x 1
- **Auto Power Off:** 10 minute.
- **Operating Temperature and Humidity:**
0°C to 40°C(32°F to 104°F); < 80%RH
- **Storage Temperature and Humidity:**
-10°C to 60°C(14°F to 140°F); < 70%RH
- **Jaw Opening Diameter:** 40mm
- **Dimensions:** 207(L)×66(W)×26(H)mm
- **Weight:** Approx. 153g
- **Accessories:**
Carrying Case, Battery, Test Lead, Instruction Manual.

*Slim
and
Lightweight
Size*

NEW!



ELECTRICAL SPECIFICATIONS

FUNCTION	RANGE	RESOLUTION	ACCURACY
ACA	600A/1000A	0.1A/1A	±1.9% ± 5dgt
ACV	6V/60V/600V	0.001V/0.01V/0.1V	±1.2% ± 5dgt
DCV	6V/60V/600V	0.001V/0.01V/0.1V	±1% ± 2dgt
Ohms	600Ω/6KΩ 60KΩ/600KΩ	0.1Ω/0.001 KΩ/ 0.01KΩ/0.1KΩ	±1% ± 2dgt
Cap.	6μF/60μF/600μF	0.001μF /0.01μF /0.1μF	±3% ± 10dgt
Hz(A)	600Hz/6KHz	0.1Hz/0.001KHz	±0.2% ± 2dgt
Hz(V)	600Hz/6KHz/60KHz	0.1Hz/0.001KHz/0.01KHz	±0.2% ± 2dgt
Duty Cycle(%)	1~99%	0.1%	±0.5%

FUNCTION	CENTER 27	CENTER 28
ACA	●	●
ACV	●	●
DCV	●	●
Ohms	●	●
Cap.		●
Hz(A)		●
Hz(V)		●
Duty Cycle(%)		●
Min/Max	●	
Peak		●

* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®
CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
New Taipei City 238, Taiwan
TEL: 886-2-26763926 E-Mail : center@centertek.com
FAX: 886-2-26763925 http : //www.centertek.com

Distributed by: