

CENTER 266 AC Leakage Clamp Meter


FEATURES

- 0.001 mA Current Resolution.
- Comply with IEC61557-13: Class 2, ≤ 30 A/m
- True RMS Measurement For All Applications.
- Low Pass Filter Function.
- Backlight Function.
- Peak Hold Function.
- Data Hold Function.
- Zero Function.
- Auto Power Off.
- Autoranging.

★ 0.001 mA!

GENERAL SPECIFICATIONS

- **Numerical Display:**
4 digital liquid crystal(LCD), Maximum reading 6000.
- **Low Battery Indication:** The  is displayed.
- **Sampling Rate:** 2 Times/sec
- **Power Source:** 1.5V size AAA battery x 2
- **Auto Power Off:** 30 minute.
- **Operating Temperature and Humidity:**
0°C to 40°C(32°F to 104°F); < 80%RH
- **Storage Temperature and Humidity:**
-10°C to 60°C(14°F to 140°F); < 80%RH
- **Jaw Opening Diameter:** 23 mm
- **Dimensions/ Weight:** 206(L)×76(W)×33.5(H)mm/ Approx.270g
- **Accessories:**
Carrying Case, Batteries, Test Lead, Instruction Manual.



LED Back Light



ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACmA	6.000mA/60.00mA/600.0mA	0.001mA/0.01mA/0.1mA	$\pm 1\% \text{rdg} \pm 3 \text{dgt}$
ACA	6.000A/60.00A	0.001A/0.01A	$\pm 1\% \text{rdg} \pm 3 \text{dgt}$
DCV	60V/600V	0.01V/0.1V	$\pm 1\% \text{rdg} \pm 2 \text{dgt}$
ACV	60V/600V	0.01V/0.1V	$\pm 1\% \text{rdg} \pm 3 \text{dgt}$
Ohm	600/6K/60K/600K Ω	0.1 Ω /1 Ω /10 Ω /100 Ω	$\pm 1\% \text{rdg} \pm 2 \text{dgt}$
$\cdot \cdot \cdot \cdot \cdot$	< 60 Ω		

CENTER
CENTER TECHNOLOGY CORP.



4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
New Taipei City 238, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http: //www.centertek.com

* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by: