# **CENTER 265 AC Leakage Clamp Meter**

CENTER 265 LEAKAGE GLAMP NET

mA

OFF

ZERO

CE

Alle.

PEAK

·11/ Ω

HOLD

HOLD

LPF

LU.JUma

CENTER

# FEATURES:

• 0.001 mA Current Resolution.

- True RMS Measurement For All Applications.
- Backlight Function.
- Low Pass Filter Function.

 $(\mathbf{R})$ 

- Peak Hold Function.
- Data Hold Function.
- Zero Function.
- Auto Power Off.
- Autoranging.

# CENTER 265 AC Leakage Clamp Meter

#### FEATURES

- 0.001 mA Current Resolution.
- **True RMS Measurement For All Applications.**
- Low Pass Filter Function.
- **Backlight Function.**
- **Peak Hold Function.**
- **Data Hold Function.** •
- Zero Function.
- Auto Power Off.
- Autoranging.

### GENERAL SPECIFICATIONS

Numerical Display: 4 digital liquid crystal(LCD), Maximum reading 6000.

- Low Battery Indication: The 📑 is displayed.
- Sampling Rate: 2 Times/sec
- **Power Source:** 1.5V size AAA battery x 2
- Auto Power Off: 30 minute.
- **Operating Temperature and Humidity:** 0°C to 40°C(32°F to 104°F); < 80%RH
- **Storage Temperature and Humidity:** -10°C to 60°C(14°F to 140°F); < 80%RH
- Jaw Opening Diameter: 23 mm
- Dimensions/ Weight: 206(L)×76(W)×33.5(H)mm/ Approx.270g •
- Accessories: Carrying Case, Batteries, Test Lead, Instruction Manual.

## **ELECTRICAL SPECIFICATIONS**

Function	Range	Resolution	Accuracy
ACmA	6.000mA/60.00mA/600.0mA	0.001mA/0.01mA/0.1mA	±1%rdg± 3dgts
ACA	6.000A/60.00A	0.001A/0.01A	±1%rdg± 3dgts
DCV	60V/600V	0.01V/0.1V	±1%rdg± 2dgts
ACV	60V/600V	0.01V/0.1V	±1%rdg± 3dgts
Ohm	<b>600/6K/60K/600K</b> Ω	0.1Ω/1Ω/10Ω/100Ω	±1%rdg± 2dgts
->))	< <b>60</b> Ω		

CENTER CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist., New Taipei City 238, Taiwan TEL: 886-2-26763926 E-Mail : center@centertek.com FAX: 886-2-26763925 http ://www.centertek.com

\* The specifications and other information in this catalogue are subject to change without prior notice.



Authorized Distributor APL ASIA CO., LTD. 11/129-132 Moo.5 Lamlukka Rd.,T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand. TEL. 0-2995-4461-3, FAX. 0-2995-4464 www.apl-asia.com EMAIL : sales@apl-asia.com LINE@ : @APL-ASIA



600V

AT II

LED Back Light

C E