


FEATURES



- 1mA Current Resolution
- True-RMS Measurement For All Applications
- AC+DC True RMS Measurements
- Built-in LED Work Light
- Backlight Function
- Data Hold Function
- Zero Function
- Auto Power Off
- Autoranging



LED Back Light



GENERAL SPECIFICATIONS

- **Sampling Rate:** 2 Times/sec
- **Power Source:** 1.5V size AAA battery x 2
- **Jaw Opening Diameter:** 20 mm
- **Dimensions/ Weight:** 232(L)×72(W)×35(H)mm/ Approx.230g
- **Accessories:** Carrying Case, Batteries, Test Lead, Instruction Manual.

ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
DC/AC mA	4000mA	1mA	±(2.0%rdg + 5dgt)
DC/AC A	40.00A / 200.0A	0.01A / 0.1A	±(2.0%rdg + 5dgt)
AC+DC mA/A	4000mA / 40.00A / 200.0A	1mA / 0.01A / 0.1A	±(2.5%rdg + 5dgt)
DCV	6.000V / 60.00V / 600.0V	0.001V / 0.01V / 0.1V	±(1.0%rdg + 2dgt)
ACV	6.000V / 60.00V / 600.0V	0.001V / 0.01V / 0.1V	±(1.2%rdg + 5dgt)
AC+DC V	6.000V / 60.00V / 600.0V	0.001V / 0.001V / 0.1V	±(1.2%rdg + 5dgt)
Capacitance	1.000uF / 10.00uF / 100.0uF / 1000uF	0.001uF / 0.01uF / 0.1uF / 1uF	±(3.0%rdg + 8dgt)
Diode	2.000V	0.001V	±(2.0%rdg + 5dgt)
Ohm	600.0Ω / 6.000KΩ / 60.00KΩ / 600.0KΩ	0.1Ω / 0.001KΩ / 0.01KΩ / 0.1KΩ	±(1.0%rdg + 3dgt)
Beeper	600.0Ω	0.1Ω	on < 140Ω, off > 110Ω

*The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®

CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
New Taipei City 238, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com



Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand.
TEL. 0-2995-4461-3, FAX. 0-2995-4464
www.apl-asia.com
EMAIL: sales@apl-asia.com
LINE@: @APL-ASIA