

CENTER 232 AC/DC TRUE RMS Power Clamp Meter



 LED Back Light



FEATURES:

- 4 Digital Display
- TRUE RMS
- Auto Power Off
- Peak Hold Function
- Data Hold Function
- Auto Zero

SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACA	600A	100mA	$\pm 2\%rdg + 10dgts$
DCA	600A	100mA	$\pm 2\%rdg + 10dgts$
ACV	600V	0.1V	$\pm 1.5\%rdg + 5dgts$
DCV	600V	0.1V	$\pm 1.5\%rdg + 5dgts$
WATT	100KW / 360KW	10W	$\pm 2\%rdg + 10dgts$
Resistor	10K Ω	1 Ω	$\pm 1.5\%rdg + 3dgts$

Battery	1.5V, size AAA battery x 2
Dimensions	218x64x30 mm
Weight	approx. 270g
Jaw Opening Diameter	30 mm

CENTER 235 AC Leakage Clamp Meter



 LED Back Light



FEATURES:

- 4 Digital Display
- 10uA Resolution
- Auto Power Off
- Autoranging
- Peak Hold Function
- Data Hold Function
- Auto Zero

SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACmA	60mA / 600mA	10uA	$\pm 2\%rdg + 10dgts$
ACA	10A / 100A	1mA	$\pm 2\%rdg + 10dgts$
DCV	600V	0.1V	$\pm 1\%rdg + 2dgts$
ACV	600V	0.1V	$\pm 1.2\%rdg + 5dgts$
Freq	1000Hz	0.1Hz	$\pm 0.5\%rdg + 2dgts$
Resistor	1000 Ω	0.1 Ω	$\pm 1\%rdg + 3dgts$

Battery	1.5V, size AAA battery x 2
Dimensions	218x64x30 mm
Weight	approx. 270g
Jaw Opening Diameter	28 mm

CENTER® **CENTER TECHNOLOGY CORP.**

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan

TEL: 886-2-26763926 E-Mail: center@centertek.com FAX: 886-2-26763925 <http://www.centertek.com>