

**FEATURES**

This unit used newly developed semi-conductor sensor which is extremely sensitive to variety of general used Combustible Gases.

Microprocessor Control with advanced digital signal processing.

**SPECIFICATIONS**

- Heated Semiconductor Gas Sensor.
- High-Low Leak Sensitivity Selector.
- 7 LED Tri-colored Visual Leak Level Indicator.
- Variable Intensity Audible Alarm.
- Ambient Concentration Reset.
- 15.5"(40CM) Flexible Stainless Probe.
- Detection of METHANE/HYDROCARBON..... Combustible Gases.
- Sensitivity As Small 5 ppm.
- Low Battery Indication.
- Reference Leak Source Included.
- Hard Carrying case Included.
- Warm-up Time: 90 Seconds.
- Operating Temperature: 0 to 40°C (32 to 104°F)
- Size: 21.7 x 6.6 x 5.6 cm
- Weight: 400g(with batteries)
- Power Source: 4 AA Size Alkaline Batteries.
- Battery Life: Appro. 40hrs



The specifications and other information in this catalogue are subject to change without prior notice.

**CENTER®**  
**CENTER TECHNOLOGY CORP.**

4/F., NO.415, Jung-Jeng Rd., 23868 Shu-Lin, Taipei, Taiwan  
TEL: 886-2-26763926 E-Mail: center@centertek.com  
FAX: 886-2-26763925 http://www.centertek.com



Authorized Distributor  
APL ASIA CO., LTD.  
11/129-132 Moo.5 Lam Lukka Rd., T.Kookut, A.Lam Lukka, Pathumthani 12130 Thailand.  
TEL. 0-2995-4461-3, FAX. 0-2995-4464  
www.apl-asia.com  
EMAIL: sales@apl-asia.com  
LINE@: @APL-ASIA