

CENTER 31 HYGRO THERMOMETER

PRELIMINARY

FEATURES

- Large, easy-to-read dual LCD displays Humidity and Temperature.
- 3%RH humidity accuracy.
- Calibration available on site.
- Desk or wall mount.
- MAX/MIN value monitor.
- Audible and visual alarms, with adjustable set points, warns if limits are exceeded.

SPECIFICATIONS

Sensor: Humidity sensor/NTC

Measurement Range:

Temperature: -10°C~60°C; -14°F~140°F

Humidity: 5%RH~100%RH

Resolution: 0.1°C/0.1°F/0.1%RH

Accuracy:

Temperature: $\pm 0.8^{\circ}\text{C}$, 1.5°F

Humidity: $\pm 3.0\% \text{RH}$

Display: LCD, 2lines.

Measuring Interval: 15 sec.

Battery Type: 1.5V AAA size battery x 4

Battery Lifetime: Approx. one year

Operating Condition: 0°C to 60°C; 14°F~140°F

Dimensions: 139(L)×102(W)×37(H)mm /180g

Accessories: Batteries, Instruction Manual

CE



Back stand with hanging support.



33%RH / 75%RH Humidity Standard (OPTIONAL)

* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER[®]
CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com



Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lam Lukka Rd., T.Kookut, A.Lam Lukka, Pathumthani 12130 Thailand.
TEL. 0-2995-4461-3, FAX. 0-2995-4464
www.apl-asia.com
EMAIL: sales@apl-asia.com
LINE@: @APL-ASIA