

CENTER 315/316 HUMIDITY TEMPERATURE METER



CE

Features:

- Dew Point and Wet Bulb Temperature Measurement. (316)
- Fast response.
- Auto shut off for Battery Saving.
- REL Function. (315)
- MAX/MIN Function.
- Dual displays:
Primary display for Humidity;
Secondary displays for Temperature.

CENTER®

CENTER 315/316 HUMIDITY TEMPERATURE METER

FEATURE


- Dew Point and Wet Bulb temperature Measurement.(316)
- Fast response.
- Auto shut off for Battery Saving.
- REL Function.(315)
- MAX/MIN Function.
- Dual displays:
Primary display for Humidity; Secondary displays for temperature.

Dual Display

CENTER 315



CENTER 316



SPECIFICATIONS

- **Measurement Range:**
Temperature: -20°C~60°C ; -4°F~140°F
Humidity: 0%RH~100%RH
- **Resolution:**
0.1°C/0.1°F/0.1%RH
- **Accuracy:**
Temperature: ±0.8°C , 1.6°F
Humidity: ±3.0%RH
- **Sampling Rate:** 2 times/sec
- **Battery Type:**
9V, NEDA 1604, IEC 6F22, JIS 006P
- **Operating Condition:**
0°C to 40°C (<80%RH)
- **Dimensions:**
240×54×34mm
- **Accessories:**
Battery, Instruction Manual



33%RH / 75%RH
Humidity Standard
(OPTIONAL)



* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER[®]
CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com



Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lam Lukka Rd., T.Kookut, A.Lam Lukka, Pathumthani 12130 Thailand.
TEL. 0-2995-4461-3, FAX. 0-2995-4464
www.apl-asia.com
EMAIL: sales@apl-asia.com
LINE@: @APL-ASIA