MAXI ECO FLOWATCH®



Maxi solenoid pump, compact and powerful, for the condensate removal of air conditioners up to 30kW / 100 000BTU.

Ref: DE40LCC300







48.5 mm



SPECIFICATIONS

FLOWRATE

Flowrate max Suction head max

Discharge head

Electrical power

Voltage

Alarm*

Noise level**

Power cable

Dimensions

Protection rating

Thermal protection

Operating cycle***

* Alarm option available on request.

m

12

11

10 9 8

7

6

1

0

10

5

20 25 30 35 40 I/h

15

** Notation from 1 wave (≤ 20 dBA) to 6 waves (> 45 dBA) *** The pump is able to run 100% of the time if necessary.

40 l/h

2 m

10 m

16W 220-240V 50/60Hz


No alarm


IP20

Yes 100%

1.5 m

111 x 41 x 48 mm / 90 x 32 x 42 mm





Hose diameter Suction: 6/9 mm - not supplied Discharge: 6/9 mm - not supplied

BENEFITS



Silent

The only pump of the world to offer such a flowrate with such a low noise.



High efficiency

Flowrate 40 l/h Discharge head 10 m



Removable reservoir

Can be easily unclipped in order to clean the reservoir and the float.



Integrated filter

Plastic filter integrated to the reservoir. It prevents big impurities to damage the pump.



Accessories included

All necessary accessories are included in the box.



Compact pump

Very small, pump and reservoir are easy to install.



CONTENTS

Pump - Reservoir - Double-side adhesive for



reservoir fixing - Inlet tube - 3 clamps



Authorized Distributor APL ASIA CO., LTD. 11/129-132 Moo.5 Lamlukka Rd., T. Kookut, A. Lamlukka, Pathumthani 12130 Thailand. TEL. 0-2995-4461-3, FAX. 0-2995-4464 www.apl-asia.com EMAIL : sales@apl-asia.com LINE@ : @APL-ASIA